



NORTHERN EASYTANK

Features & Benefits:

TANK

Standard Features:

- 500 – 20,000 Gallon Capacity
- Premium Polyethylene Vertical & Horizontal Storage Tanks
- 2" Layer Closed Cell Foam Insulation
- ISO 22241 Compliant

CABINET

Mounted Dispense Cabinet Features:

- 24" W x 48" H x 25" D
- ULC TD10-115V Diaphragm Pump
- Turbine Flow Meter
- 25' Hose Reel
- 650W Heater with Auto Thermostat
- Digital Liquid Level Indicator
- 2" Camlock Fill

ELECTRICAL REQUIREMENTS

- Requires 115V Circuit
- 30 Amp Dedicated Breaker

SITE REQUIREMENTS

- Must be installed on level surface
- Crash Protection is recommended
- Additional requirements may be necessary depending upon local or state regulations



Optional Features:

- Tank Heat Tracing – Maintains a ΔT of 40°F
- Pulse Meter
For use with fuel management systems
- 2" Standpipe for Tank Monitor Probe
- Submersible Pump
For use with multiple dispense points
- 50' Hose Reel



PART #	GALLONS	SHIPPING WEIGHT (LBS)	TANK DIMENSIONS (Dia x Height)	CABINET DIMENSIONS (WxHxD)
905-013-5	500	425	52" x 75"	24" x 48" x 25"
905-017-6	750	488	52" x 105"	24" x 48" x 25"
905-019-5	850	533	52" x 120"	24" x 48" x 25"
905-015-8	1000	514	68" x 82"	24" x 48" x 25"
905-041-3	1050	600	52" x 136"	24" x 48" x 25"
905-012-3	1500	689	68" x 118"	24" x 48" x 25"
905-042-3	2000	860	68" x 154"	24" x 48" x 25"
905-043-3	2100	688	91" x 91"	24" x 48" x 25"
905-044-3	3000	892	99" x 111"	24" x 48" x 25"

*Tank dimensions include foam insulation and wrap.